








# CAR PRODUCTS APRIL 2023

MODEL	DESCRIPTION	UNIT	
<p>WF 200</p> 	<p>Mid-woofer 200mm, cono in cellulosa, Sospensione gomma, bobina mobile 38mm Magnete ferrite da 105mm</p>	<p>pair</p>	
<p>W165.25</p> 	<p>Mid-woofer 165mm, cono fibra di vetro, Sospensione gomma a doppia onda, bobina mobile 25mm Magnete ferrite da 80mm</p>	<p>pair</p>	
<p>W165.32C</p> 	<p>Mid-woofer 165mm, cono in cellulosa, Sospensione gomma, bobina mobile 32mm Magnete ferrite 105mm</p>	<p>pair</p>	
<p>W165.38</p> 	<p>Mid-woofer 165mm, cono in cellulosa, sospensione gomma a doppia onda, bobina mobile 38mm Magnete ferrite da 105mm + Neodimio</p>	<p>pair</p>	



# CAR PRODUCTS APRIL 2023

MODEL	DESCRIPTION	UNIT	
<p>MWX 165</p> 	<p><b>Mid-woofer 165mm, cono in cellulosa, Sospensione gomma, bobina mobile 32mm Magnete ferrite 105mm</b></p>	<p>pair</p>	
<p>MW 6.4</p>	<p><b>Mid-woofer, cono cellulosa trattata, Sospensione gomma, bobina mobile 25mm Impedenza 4 ohm</b></p>	<p>pair</p>	
<p>HMX 94</p> 	<p><b>Midrange 87mm, cono cellulosa trattata, Sospensione gomma, bobina mobile 25mm, Impedenza 4 ohm Magnete Neodimio</b></p>	<p>pair</p>	
<p>MX 35</p> 	<p><b>Midrange 87mm, cono cellulosa trattata, Sospensione gomma, bobina mobile 25mm</b></p>	<p>pair</p>	

# CAR PRODUCTS APRIL 2023

MODEL	DESCRIPTION	UNIT	
T 2 	<b>Tweeter cupola seta, bobina mobile 20mm Ferrofluido.</b>	pair	
T 25 	<b>Tweeter cupola seta, bobina mobile 25mm Ferrofluido. 4 ohm</b>	pair	
TW 25FL 	<b>Tweeter cupola seta, bobina mobile 25mm Ferrofluido Profilo catenario. 6ohm</b>	pair	
TW 28C	<b>Tweeter cupola seta, bobina mobile 28mm Camera di risonanza posteriore</b>	pair	

# CAR PRODUCT APRIL 2023

MODEL	DESCRIPTION	UNIT	
SW 10.4 	Subwoofer 10" cono in cellulosa, bobina da 64mm, 4 ohm	piece	
SW 12.22 	Subwoofer 12" cono cellulosa, bobina da 75mm, 2 + 2 ohm	piece	

Silence.lab

# CAR PRODUCTS APRIL 2023

MODEL	DESCRIPTION	UNIT	
HD 1.0 DSP	<p>DSP hi-end , 10 ch uscita, input: 5ch x rca 8ch Hi-Level 2 x spdif coax 1 x optical 192Khz/24Bit all chain</p>	piece	
E-DSP8	<p>DSP 8 ch out 4V 6 x analog input 1 x digital coax Bluetooth Aptx HD App BT per controllo remoto</p>	piece	
A-DSP800	<p>Amplificatore 8 x 100W con dsp a 10 ch 8ch in analog 1 x digital coax Bluetooth Aptx HD USB audio 8ch out 100W @ 4ohm 2ch line out</p>	piece	N.D.
H-DSP10	<p>DSP 10ch out A2B Tech</p>	ND	ND



# CAR PRODUCTS APRIL 2023

MODEL	DESCRIPTION	UNIT	
SQ 70.4 	<b>Amplificatore 4 canali senza CrossOver</b> 4 x 70 W @ 4 ohm 4 x 90 W @ 2 ohm 2 x 180 W @ 4 ohm bridged THD < 0.02%, S/N 90 dB Risposta in Frequenza 10Hz – 40 Khz +/- 1 dB Classe AB - Finali Mosfet Dimensioni 58x180x230 mm	piece	
SQ 150.4 	<b>Amplificatore 4 canali senza CrossOver</b> 4 x 146 W @ 4 ohm 4 x 225 W @ 2 ohm 2 x 450 W @ 4 ohm bridged THD < 0.1%, S/N 90 dB Risposta in Frequenza 10Hz – 40 Khz +/- 1 dB Classe AB - Finali Mosfet Dimensioni 58x180x424 mm	piece	
SQ 250.4 	<b>Amplificatore 4 canali senza CrossOver</b> 4 x 241 W @ 4 ohm 4 x 370 W @ 2 ohm 2 x 740 W @ 4 ohm bridged THD < 0.1%, S/N 90 dB Risposta in Frequenza 10Hz – 40 Khz +/- 1 dB Classe AB - Finali Mosfet Dimensioni 58x180x546 mm	piece	
SQ 280.2 	<b>Amplificatore 2 canali senza CrossOver</b> 2 x 285 W @ 4 ohm 2 x 470 W @ 2 ohm 1 x 940 W @ 4 ohm bridged THD < 0.1%, S/N 90 dB Risposta in Frequenza 10Hz – 40 Khz +/- 1 dB Classe AB - Finali Mosfet Dimensioni 58x180x546 mm	piece	